

Intrusion Panels

IC60 Keypads, Remote Controls and Card Readers

Keypads



Type

Order No.

IKP6-03

Wireless LED keypad



The IKPW6-10 is a wireless keypad for SiWay enabled panels. It enables the same functionality as a remote control for easy system setting/unsetting, and also supports user codes for uncompromised security. Besides, home automation functions can be controlled from anywhere in the premises, thanks to the keypad dedicated commands and the panel's programmable outputs. Panic alarms are also supported.

Power supply	9 – 16 VDC (via central bus)
Current consumption	Min. 40 mA Typ. 70 mA Max. 110 mA
Bus connection for	2 x central bus (up to 8)
LCD Display	LCD 2 x 16 characters
Operating temperature	-10 ~ +50 °C
Housing material	ABS-V0 white
Housing protection	IP41
Dimensions (W x H x D)	145 x 126 x 22 mm
Weight	Ca 0.300 kg
Standard / approval	EN 50131: Grade 2, Class II
Data sheet	009093

A5Q00020290

IKP6-03B

External LCD keypad black with large display and temperature indication



The keypad benefits from a stylish and slim-line design. The glossy finish, the crystal clear buttons and the black color will cater for every style and taste. The IKP6-03 is equipped with an extra large 2-line display, each line consisting of 16 characters. The display and keys are backlit, and the intensity of the illumination, as well as the volume of the signal tones, can be individually adjusted. The 5 LED's display the most important system statuses such as "ready", "trouble", "stay at home", "bypass" and "armed". The keypad layout mirrors the familiar telephone dials for ultimate user-friendliness, and clearly shows separate emergency call buttons. A room temperature indication is also integrated.
Color: black

Power supply	9 – 16 VDC (via central bus)
Current consumption	Min. 40 mA Typ. 70 mA Max. 110 mA
Bus connection for	2 x central bus (max. 8)
LCD Display	LCD 2 x 16 characters
Operating temperature	-10 ~ +50 °C
Housing material	ABS-V0 black
Housing protection	IP41
Dimensions (W x H x D)	145 x 126 x 22 mm
Weight	Ca 0.300 kg
Standard / approval	EN 50131: Grade 2, Class II
Data sheet	009093

S54543-F105-A100

15